Control Access Distribution
326 avenue de la Rasclave - 13821 La Penne-sur-Huveaune - France
04 91 18 82 68 | cad@controlaccessdistri.com | controlaccesspro.com

BSO **RÉNO**

BON DE COMMANDE

CACHET DU CLIENT

ADRESSE DE LIVRAISON *(si différente)*

TÉLÉCOPIE : 03 88 18 10 18

MARQUISES®
Les stores les plus en vue de France

RÉFÉRENCE CLIENT : _____

N° DE COMMANDE : _____

DATE :

COMPTE N° :

Type de BSO : **Coloris lames :** **Coloris lames finale :** **Potences :** **Coulisse :**

Coloris caisson : **Coloris manivelle :** ☐ Gris (standard - sans précision de votre part) ☐ Blanc

Repère	Nombre	Taille de caisson		① Dimensions du store (mm) dos de coulisse et coffre inclus		Type de manœuvre		Coté de commande (vue intérieure)			Définition de la manœuvre treuil						④ Types de coulisses			
											② Position du treuil °/.	Sortie directe (+)	Sortie		Fin de course (+)	Longueur manivelle	Type de pose gauche		Type de pose droite	
		205	254	Largeur	Hauteur	Moteur	Treuil	GA	MI	DR			45°	(+) 90°			Face	Baie	Face	Baie

Équipements optionnels

Automatisme radio RTS	Qtés
☐ **Ensemble Récepteur radio RTS MI/MU** (par BSO) avec télécommande portable 1 canal à molette	
☐ **Ensemble Récepteur radio RTS MI/MU** (par BSO) Émetteur mural Smoove RTS 1 canal	
☐ **Télécommande portable 4 canaux Pure à molette (seule)**	
☐ **Récepteur radio RTS MI/MU seul** (par BSO)	

Moteur filaire Geiger	Qtés
☐ Moteur Duo Drive - moteur rapide 6N	

Point de commande et automatismes pour moteur filaire	Qtés
☐ Inverseur orienta INIS UNO encastré (par BSO)	
☐ Boitier inverseur pose saillie (par inverseur)	

Automatismes	Qtés
☐ Solution Animéo (compléter p.79)	
☐ Autres automatismes (compléter bdc p.79)	

Toute commande renferme acceptation sous réserve de nos Conditions Générales de Vente (visible p.116 ou sur le site www.stores-marquises.fr), et notamment de la clause de réserve de propriété qui y est incluse.

Automatisme Radio IO	Qtés
☐ **Moteur Somfy Radio IO** (par BSO) avec portable Situo IO 1 canal à variation	
☐ **Émetteur portable Situo io 5 canaux à variation**	
☐ **Émetteur mural Sensitive IO 1 canal**	

Accessoires	Qtés
☐ Équerre en L (fixation BSO de face sans caisson)	

CONTROL ACCESS DISTRIBUTION

Control Access Distribution
326 avenue de la Rasclave · 13821 La Penne-sur-Huveaune · France
04 91 18 82 68 · cad@controlaccessdistri.com · controlaccesspro.com

Documentary translation · English

Source: BSO Réno — manufacturer form,2016 archive

Reading key to the archived 2016 manufacturer form. The original order form is preserved. Its options and terms belong to this historical source; confirm the current configuration.

BSO RÉNO — ORDER FORM

Customer stamp; delivery address (if different); date; account No.; customer reference; order No.

Fax: 03 88 18 10 18. France's most prominent blinds.

BSO type; slat colour; bottom rail colour; support brackets; guide rail.

Headbox colour.

Crank colour: Grey (standard, unless you specify otherwise); White.

1 Blind dimensions (mm)

Item ID; quantity; width; height; including guide-rail back and headbox.

Headbox size: 205; 254.

Operating method: Motor; Crank.

Control side (inside view): GA; MI; DR.

Crank operation specification

2 Gearbox position + / -.

Direct outlet (+); outlet: 45° or (+) 90°; end limit (+); crank length.

4 Guide rail types

Left mounting type: Face; Recess.

Right mounting type: Face; Recess.

Printed folio 49.

CONTROL ACCESS DISTRIBUTION

Control Access Distribution
326 avenue de la Rasclave · 13821 La Penne-sur-Huveaune · France
04 91 18 82 68 · cad@controlaccessdistri.com · controlaccesspro.com

Documentary translation · English

Source: BSO Réno — manufacturer form,2016 archive

Optional equipment

RTS radio controls — Qty

RTS MI/MU radio receiver set (per BSO), with a 1-channel hand-held remote with scroll wheel.

RTS MI/MU radio receiver set (per BSO) — 1-channel Smoove RTS wall transmitter.

4-channel Pure hand-held remote with scroll wheel (alone).

RTS MI/MU radio receiver only (per BSO).

Control points and automation for wired motors — Qty

Flush-mounted orienta INIS UNO reversing switch (per BSO).

Surface-mount reversing switch box (per switch).

IO radio controls — Qty

Somfy IO radio motor (per BSO), with a 1-channel Situo IO hand-held remote with adjustment.

5-channel Situo io hand-held transmitter with adjustment.

1-channel Sensitive IO wall transmitter.

Geiger wired motor — Qty

Duo Drive motor - high-speed motor 6N.

Automation — Qty

Animéo solution (complete p.79).

Other automation (complete order form p.79).

Accessories — Qty

L-bracket (face mounting of BSO without headbox).

Placing an order constitutes acceptance of our General Terms and Conditions of Sale (available on p.116 or at www.stores-marquises.fr), in particular the retention-of-title clause included in them.

CONTROL ACCESS DISTRIBUTION